



Somente ferramentas corte à direita.

TIPO ÁRVORE

A.R : -7°—+5°
R.R : -15°—0°

Arestia de Corte (R)	Referência para Pedido	R	Estoque	Nº de Dentes	Dimensões*(mm)							Peso da Ferramenta (kg)	Máx. Prof. de Corte (mm)		Tipo (Fig.)		
					D1	D6	D7	L1	D9	L7	D8		W1	L8		ap	A2
6	BRP6P-040A03R	★	3	3	40	27.9	33.3	40	16	18	—	8.4	5.6	0.4	6	4	1
	-050A04R	★	4	4	50	37.8	43.1	50	22	20	11	10.4	6.3	0.5	6	4	2
	R05004B	★	4	4	50	37.8	43.1	63	22.225	29	11	8.4	5	0.5	6	4	2
	-063A05R	★	5	5	63	50.8	56.1	50	22	20	11	10.4	6.3	0.7	6	4	2
	R06305B	●	5	5	63	50.8	56.1	63	22.225	29	11	8.4	5	0.7	6	4	2
	R08006C	●	6	6	80	67.8	72.8	50	25.4	26	13	9.5	6	1.2	6	4	2
8	BRP8P-063A04R	★	4	4	63	46.8	54.5	50	22	20	11	10.4	6.3	0.7	8	5.5	2
	R06304B	●	4	4	63	46.8	54.5	63	22.225	29	11	8.4	5	0.7	8	5.5	2
	R08005C	●	5	5	80	63.8	70.9	50	25.4	26	13	9.5	6	1.2	8	5.5	2
	R10006D	●	6	6	100	83.8	90.6	50	31.75	32	45	12.7	8	1.6	8	5.5	3

ACESSÓRIOS

Referência da Ferramenta	**	**	**	① ②
	Parafuso de Fixação	Chave	Parafuso de Montagem	Inserto
BRP6P-040A03R	TS43	TKY15D	HDS08030	
BRP6P-050A04R BRP6P-R08006C	TS43	TKY15D	—	①RPMW1204M0 ②RPMT1204M0E-JS
BRP8P	TS54	TKY25D	—	①RPMW1606M0 ②RPMT1606M0E-JS

* Torque de Fixação (N • m) ** TS43=3.5, TS54=7.5