



INSERTOS

(Ferro Fundido)



Referência para Pedido	Estoque		Dimensões (mm)			Suporte Correspondente
	DP5010		D1	L2	S1	
NEW STAWK1000TG	●		10.0	3.3	4.6	STAWSS1000S16
NEW 1010TG	●		10.1	3.3	4.6	STAWSN1000S16
NEW 1020TG	●		10.2	3.3	4.6	STAWMN1000S16
NEW 1030TG	●		10.3	3.3	4.6	STAWLN1000S16
NEW 1040TG	●		10.4	3.3	4.6	
NEW 1050TG	●		10.5	3.5	4.8	STAWSS1050S16
NEW 1060TG	●		10.6	3.5	4.8	STAWSN1050S16
NEW 1070TG	●		10.7	3.5	4.8	STAWMN1050S16
NEW 1080TG	●		10.8	3.5	4.8	STAWLN1050S16
NEW 1090TG	●		10.9	3.5	4.8	
NEW 1100TG	●		11.0	3.7	5.1	STAWSS1100S16
NEW 1110TG	●		11.1	3.7	5.1	STAWSN1100S16
NEW 1120TG	●		11.2	3.7	5.1	STAWMN1100S16
NEW 1130TG	●		11.3	3.7	5.1	STAWLN1100S16
NEW 1140TG	●		11.4	3.7	5.1	
NEW 1150TG	●		11.5	3.9	5.3	STAWSS1150S16
NEW 1160TG	●		11.6	3.9	5.3	STAWSN1150S16
NEW 1170TG	●		11.7	3.9	5.3	STAWMN1150S16
NEW 1180TG	●		11.8	3.9	5.3	STAWLN1150S16
NEW 1190TG	●		11.9	3.9	5.3	
NEW 1200TG	●		12.0	4.1	5.5	STAWSS1200S16
NEW 1210TG	●		12.1	4.1	5.5	STAWSN1200S16
NEW 1220TG	●		12.2	4.1	5.5	STAWMN1200S16
NEW 1230TG	●		12.3	4.1	5.5	STAWLN1200S16
NEW 1240TG	●		12.4	4.1	5.5	
NEW 1250TG	●		12.5	4.2	5.8	STAWSS1250S16
NEW 1260TG	●		12.6	4.2	5.8	STAWSN1250S16
NEW 1270TG	●		12.7	4.2	5.8	STAWMN1250S16
NEW 1280TG	●		12.8	4.2	5.8	STAWLN1250S16
NEW 1290TG	●		12.9	4.2	5.8	
NEW 1300TG	●		13.0	4.4	6.0	STAWSS1300S16
NEW 1310TG	●		13.1	4.4	6.0	STAWSN1300S16
NEW 1320TG	●		13.2	4.4	6.0	STAWMN1300S16
NEW 1330TG	●		13.3	4.4	6.0	STAWLN1300S16
NEW 1340TG	●		13.4	4.4	6.0	
NEW 1350TG	●		13.5	4.6	6.2	STAWSS1350S16
NEW 1360TG	●		13.6	4.6	6.2	STAWSN1350S16
NEW 1370TG	●		13.7	4.6	6.2	STAWMN1350S16
NEW 1380TG	●		13.8	4.6	6.2	STAWLN1350S16
NEW 1390TG	●		13.9	4.6	6.2	

S-TAW

Broca intercambiável de diâmetro pequeno

Referência para Pedido	Estoque		Dimensões (mm)			Suporte Correspondente
	DP5010		D1	L2	S1	
NEW STAWK1400TG	●		14.0	4.8	6.4	STAWSS1400S16 STAWSN1400S16 STAWMN1400S16 STAWLN1400S16
NEW 1410TG	●		14.1	4.8	6.4	
NEW 1420TG	●		14.2	4.8	6.4	
NEW 1430TG	●		14.3	4.8	6.4	
NEW 1440TG	●		14.4	4.8	6.4	
NEW 1450TG	●		14.5	5.0	6.7	STAWSS1450S16 STAWSN1450S16 STAWMN1450S16 STAWLN1450S16
NEW 1460TG	●		14.6	5.0	6.7	
NEW 1470TG	●		14.7	5.0	6.7	
NEW 1480TG	●		14.8	5.0	6.7	
NEW 1490TG	●		14.9	5.0	6.7	
NEW 1500TG	●		15.0	5.2	6.9	STAWSS1500S20 STAWSN1500S20 STAWMN1500S20 STAWLN1500S20
NEW 1510TG	●		15.1	5.2	6.9	
NEW 1520TG	●		15.2	5.2	6.9	
NEW 1530TG	●		15.3	5.2	6.9	
NEW 1540TG	●		15.4	5.2	6.9	
NEW 1550TG	●		15.5	5.3	7.1	STAWSS1600S20 STAWSN1600S20 STAWMN1600S20 STAWLN1600S20
NEW 1560TG	●		15.6	5.3	7.1	
NEW 1570TG	●		15.7	5.3	7.1	
NEW 1580TG	●		15.8	5.3	7.1	
NEW 1590TG	●		15.9	5.3	7.1	
NEW 1600TG	●		16.0	5.3	7.1	
NEW 1610TG	●		16.1	5.3	7.1	
NEW 1620TG	●		16.2	5.3	7.1	
NEW 1630TG	●		16.3	5.3	7.1	
NEW 1640TG	●		16.4	5.3	7.1	
NEW 1650TG	●		16.5	5.7	7.6	STAWSS1700S20 STAWSN1700S20 STAWMN1700S20 STAWLN1700S20
NEW 1660TG	●		16.6	5.7	7.6	
NEW 1670TG	●		16.7	5.7	7.6	
NEW 1680TG	●		16.8	5.7	7.6	
NEW 1690TG	●		16.9	5.7	7.6	
NEW 1700TG	●		17.0	5.7	7.6	
NEW 1710TG	●		17.1	5.7	7.6	
NEW 1720TG	●		17.2	5.7	7.6	
NEW 1730TG	●		17.3	5.7	7.6	
NEW 1740TG	●		17.4	5.7	7.6	
NEW 1750TG	●		17.5	6.0	8.1	STAWSS1800S20 STAWSN1800S20 STAWMN1800S20 STAWLN1800S20
NEW 1760TG	●		17.6	6.0	8.1	
NEW 1770TG	●		17.7	6.0	8.1	
NEW 1780TG	●		17.8	6.0	8.1	
NEW 1790TG	●		17.9	6.0	8.1	
NEW 1800TG	●		18.0	6.0	8.1	
NEW 1810TG	●		18.1	6.0	8.1	
NEW 1820TG	●		18.2	6.0	8.1	
NEW 1830TG	●		18.3	6.0	8.1	
NEW 1840TG	●		18.4	6.0	8.1	

FURAÇÃO

● : Estoque mantido.
(Nota: 1 inserto por embalagem)