


INSERTOS

Tipo H



Referência para Pedido	Estoque		Dimensões (mm)			Suporte Correspondente
	VPI5TF	VPI10H	D1	L2	S1	
TAWNH1400T	▲		14.0	7.6	5.0	TAWSNH 1400S16
1410T	▲		14.1	7.6	5.0	TAWMNH 1400S16
1420T	▲		14.2	7.6	5.0	TAWLNH 1400S16
1430T	▲		14.3	7.6	5.0	TAWLNH 1400S16
1440T	▲		14.4	7.6	5.0	TAWLNH 1400S16
1450T	▲		14.5	7.5	5.0	
1460T	▲		14.6	7.5	5.0	
1470T	▲		14.7	7.5	5.0	TAWSNH 1500S20
1480T	▲		14.8	7.5	5.0	
1490T	▲		14.9	7.5	5.0	TAWMNH 1500S20
1500T	▲		15.0	7.4	5.0	
1510T	▲		15.1	7.4	5.0	TAWLNH 1500S20
1520T	▲		15.2	7.4	5.0	
1530T	▲		15.3	7.4	5.0	
1540T	▲		15.4	7.4	5.0	
1550T	▲		15.5	7.9	6.0	
1560T	▲		15.6	7.9	6.0	
1570T	▲		15.7	7.9	6.0	TAWSN 1600S20
1580T	▲		15.8	7.9	6.0	
1590T	▲		15.9	7.9	6.0	TAWMN 1600S20
1600T	▲		16.0	7.8	6.0	
1610T	▲		16.1	7.8	6.0	TAWLN 1600S20
1620T	▲		16.2	7.8	6.0	
1630T	▲		16.3	7.8	6.0	
1640T	▲		16.4	7.8	6.0	
1650T	▲		16.5	7.7	6.0	
1660T	▲		16.6	7.7	6.0	
1670T	▲		16.7	7.7	6.0	TAWSN 1700S20
1680T	▲		16.8	7.7	6.0	
1690T	▲		16.9	7.7	6.0	TAWMN 1700S20
1700T	▲		17.0	7.6	6.0	
1710T	▲		17.1	7.6	6.0	TAWLN 1700S20
1720T	▲		17.2	7.6	6.0	
1730T	▲		17.3	7.6	6.0	
1740T	▲		17.4	7.6	6.0	
1750T	▲		17.5	7.5	6.0	
1760T	▲		17.6	7.5	6.0	
1770T	▲		17.7	7.5	6.0	TAWSN 1800S20
1780T	▲		17.8	7.5	6.0	
1790T	▲		17.9	7.5	6.0	TAWMN 1800S20
1800T	▲		18.0	7.4	6.0	
1810T	▲		18.1	7.4	6.0	TAWLN 1800S20
1820T	▲		18.2	7.4	6.0	
1830T	▲		18.3	7.4	6.0	
1840T	▲		18.4	7.4	6.0	

Referência para Pedido	Estoque		Dimensões (mm)			Suporte Correspondente
	VPI5TF	VPI10H	D1	L2	S1	
TAWNH1850T	●	□	18.5	9.3	7.0	
1860T	●	□	18.6	9.3	7.0	
1870T	●	□	18.7	9.3	7.0	TAWSN 1900S25
1880T	●	□	18.8	9.3	7.0	
1890T	●	□	18.9	9.3	7.0	TAWMN 1900S25
1900T	●	□	19.0	9.2	7.0	
1910T	●	□	19.1	9.2	7.0	TAWLN 1900S25
1920T	●	□	19.2	9.2	7.0	
1930T	●	□	19.3	9.2	7.0	
1940T	●	□	19.4	9.2	7.0	
1950T	●	□	19.5	9.1	7.0	
1960T	●	□	19.6	9.1	7.0	
1970T	●	□	19.7	9.1	7.0	TAWSN 2000S25
1980T	●	□	19.8	9.1	7.0	
1990T	●	□	19.9	9.1	7.0	TAWMN 2000S25
2000T	●	□	20.0	9.0	7.0	
2010T	□	□	20.1	9.0	7.0	TAWLN 2000S25
2020T	□	□	20.2	9.0	7.0	
2030T	□	□	20.3	9.0	7.0	
2040T	□	□	20.4	9.0	7.0	
2050T	●	□	20.5	8.9	7.0	
2060T	□	□	20.6	8.9	7.0	
2070T	□	□	20.7	8.9	7.0	TAWSN 2100S25
2080T	□	□	20.8	8.9	7.0	
2090T	□	□	20.9	8.9	7.0	TAWMN 2100S25
2100T	●	□	21.0	8.8	7.0	
2110T	□	□	21.1	8.8	7.0	TAWLN 2100S25
2120T	□	□	21.2	8.8	7.0	
2130T	□	□	21.3	8.8	7.0	
2140T	□	□	21.4	8.8	7.0	
2150T	●	□	21.5	10.6	8.0	
2160T	□	□	21.6	10.6	8.0	
2170T	□	□	21.7	10.6	8.0	TAWSN 2200S25
2180T	□	□	21.8	10.6	8.0	
2190T	□	□	21.9	10.6	8.0	TAWMN 2200S25
2200T	●	□	22.0	10.5	8.0	
2210T	□	□	22.1	10.5	8.0	TAWLN 2200S25
2220T	□	□	22.2	10.5	8.0	
2230T	□	□	22.3	10.5	8.0	
2240T	□	□	22.4	10.5	8.0	
2250T	●	□	22.5	10.4	8.0	TAWSN 2300S25
2260T	□	□	22.6	10.4	8.0	TAWMN 2300S25
2270T	□	□	22.7	10.4	8.0	TAWLN 2300S25
2280T	□	□	22.8	10.4	8.0	
2290T	□	□	22.9	10.4	8.0	

FURAÇÃO

TAW

Referência para Pedido	Estoque		Dimensões (mm)			Suporte Correspondente
	VP15TF	VP10H	D1	L2	S1	
TAWNH2300T	●	□	23.0	10.3	8.0	TAWSN 2300S25
2310T	□	□	23.1	10.3	8.0	TAWMN 2300S25
2320T	□	□	23.2	10.3	8.0	TAWLN 2300S25
2330T	□	□	23.3	10.3	8.0	
2340T	□	□	23.4	10.3	8.0	
2350T	●	□	23.5	10.2	8.0	
2360T	□	□	23.6	10.2	8.0	
2370T	□	□	23.7	10.2	8.0	TAWSN 2400S32
2380T	□	□	23.8	10.2	8.0	TAWMN 2400S32
2390T	□	□	23.9	10.2	8.0	TAWLN 2400S32
2400T	●	□	24.0	10.1	8.0	
2410T	□	□	24.1	10.1	8.0	
2420T	□	□	24.2	10.1	8.0	
2430T	□	□	24.3	10.1	8.0	
2440T	□	□	24.4	10.1	8.0	
2450T	●	□	24.5	11.7	9.0	
2460T	□	□	24.6	11.7	9.0	
2470T	□	□	24.7	11.7	9.0	TAWSN 2500S32
2480T	□	□	24.8	11.7	9.0	TAWMN 2500S32
2490T	□	□	24.9	11.7	9.0	TAWLN 2500S32
2500T	●	□	25.0	11.6	9.0	
2510T	□	□	25.1	11.6	9.0	
2520T	□	□	25.2	11.6	9.0	
2530T	□	□	25.3	11.6	9.0	
2540T	□	□	25.4	11.6	9.0	
2550T	●	□	25.5	11.5	9.0	
2560T	□	□	25.6	11.5	9.0	
2570T	□	□	25.7	11.5	9.0	TAWSN 2600S32
2580T	□	□	25.8	11.5	9.0	TAWMN 2600S32
2590T	□	□	25.9	11.5	9.0	TAWLN 2600S32
2600T	●	□	26.0	11.4	9.0	
2610T	□	□	26.1	11.4	9.0	
2620T	□	□	26.2	11.4	9.0	
2630T	□	□	26.3	11.4	9.0	
2640T	□	□	26.4	11.4	9.0	
2650T	●	□	26.5	11.3	9.0	
2660T	□	□	26.6	11.3	9.0	
2670T	□	□	26.7	11.3	9.0	TAWSN 2700S32
2680T	□	□	26.8	11.3	9.0	TAWMN 2700S32
2690T	□	□	26.9	11.3	9.0	TAWLN 2700S32
2700T	●	□	27.0	11.2	9.0	
2710T	□	□	27.1	11.2	9.0	
2720T	□	□	27.2	11.2	9.0	
2730T	□	□	27.3	11.2	9.0	
2740T	□	□	27.4	11.2	9.0	

Referência para Pedido	Estoque		Dimensões (mm)			Suporte Correspondente
	VP15TF	VP10H	D1	L2	S1	
TAWNH2750T	●	□	27.5	12.3	10.0	
2760T	□	□	27.6	12.3	10.0	
2770T	□	□	27.7	12.3	10.0	TAWSN 2800S32
2780T	□	□	27.8	12.3	10.0	TAWMN 2800S32
2790T	□	□	27.9	12.3	10.0	TAWLN 2800S32
2800T	●	□	28.0	12.2	10.0	
2810T	□	□	28.1	12.2	10.0	
2820T	□	□	28.2	12.2	10.0	
2830T	□	□	28.3	12.2	10.0	
2840T	□	□	28.4	12.2	10.0	
2850T	●	□	28.5	12.1	10.0	
2860T	□	□	28.6	12.1	10.0	
2870T	□	□	28.7	12.1	10.0	TAWSN 2900S32
2880T	□	□	28.8	12.1	10.0	TAWMN 2900S32
2890T	□	□	28.9	12.1	10.0	TAWLN 2900S32
2900T	●	□	29.0	12.0	10.0	
2910T	□	□	29.1	12.0	10.0	
2920T	□	□	29.2	12.0	10.0	
2930T	□	□	29.3	12.0	10.0	
2940T	□	□	29.4	12.0	10.0	
2950T	●	□	29.5	11.9	10.0	
2960T	□	□	29.6	11.9	10.0	
2970T	□	□	29.7	11.9	10.0	TAWSN 3000S32
2980T	□	□	29.8	11.9	10.0	TAWMN 3000S32
2990T	□	□	29.9	11.9	10.0	TAWLN 3000S32
3000T	●	□	30.0	11.8	10.0	
3010T	□	□	30.1	11.8	10.0	
3020T	□	□	30.2	11.8	10.0	
3030T	□	□	30.3	11.8	10.0	
3040T	□	□	30.4	11.8	10.0	

FURAÇÃO

● : Estoque mantido. □ : Sem estoque, produzido somente por pedido.

▲ : Estoque mantido. Será substituído por novos produtos.

(Nota: 1 inserto por embalagem)